



SEALANT SELECTION MATRIX

Pecora sealants stocked at Altitude Construction Supply



Product	Chemistry	Parts	Grade	Movement class (%)	Service temp (°F)	Expansion & control	Door & window	Non-structural glazing	Structural glazing	Shop glazing	Window bedding	High impact	Highway	Pedestrian	Vehicular	Airfield	Parking area	Acoustical	Below grade	Firestopping	Security	Water immersion
POLYURETHANE / HYBRID																						
Dynatrol I-XL Hybrid General purpose silicone/urethane hybrid	STPU	1	Non-sag	50	-40 to 195	●	●	●														
Dynatrol I-XL FTH Field tintable silicone/urethane hybrid	STPU	1	Non-sag	50	-40 to 195	●	●															
Dynatrol II General purpose polyurethane	Urethane	2	Non-sag	50	-20 to 180	●	●							●	●		●	●	●	●	●	●
Dynatrol II-SL Self-leveling, traffic-grade polyurethane	Urethane	2	Self-leveling	50	-20 to 180	●								●	●		●					
Dynatred Non-sag, traffic-grade polyurethane	Urethane	2	Non-sag	25	-20 to 180	●	●							●	●		●		●	●		●
Urexpan NR-201 Self-leveling, traffic-grade hybrid STPU	STPU	1	Self-leveling	25	-20 to 180	●								●	●		●					
SILICONE																						
864NST Architectural silicone, non-staining	Silicone	1	Non-sag	50	-60 to 300	●	●	●												●		
890NST Ultra-low modulus architectural silicone	Silicone	1	Non-sag	100	-60 to 300	●	●	●														
890FTS Field tintable silicone	Silicone	1	Non-sag	100	-60 to 300	●	●	●														
890FTS-TXTR Field tintable textured silicone	Silicone	1	Non-sag	50	-60 to 300	●	●	●														
895NST Silicone glazing and weatherproofing	Silicone	1	Non-sag	50	-60 to 300	●	●	●	●	●	●	●										
PCS One-part architectural silicone	Silicone	1	Non-sag	50	-60 to 300	●	●	●		●	●											
HIGHWAY AND PAVEMENT SILICONE																						
300-SL Self-leveling pavement joint sealant	Silicone	1	Self-leveling	100	-60 to 300	●							●	●	●	●	●					
301-NS Non-sag pavement joint sealant	Silicone	1	Non-sag	100	-60 to 300	●							●	●	●	●	●					
ACRYLIC LATEX																						
AC-20 + Silicone Non-sag acrylic latex caulking compound	Acrylic	1	Non-sag	N/A	0 to 180		●				●											
AC-20 FTR Fire and temperature rated acoustical and insulation sealant	Acrylic	1	Non-sag	N/A	0 to 180		●											●		●		

Chemistry, grade, movement class, service temperature and application checkmarks are from Pecora's Full Line Capabilities Chart. Parts: 1 = one-part, 2 = two-part. Movement class is Pecora's ASTM C920 / C719 class in percent. Always confirm with the current Pecora product data sheet for joint design, primers and substrates. Questions on which sealant fits your joint? Call Altitude at (303) 482-1010.