



QUALIDECK SYSTEM SELECTOR

Which Qualideck traffic coating system fits the job?



	SYSTEMS			
Layer	MEDIUM DUTY	HEAVY DUTY	EXTRA HEAVY DUTY	EXTREME DUTY
Primer	4 mils	4 mils	4 mils	4 mils
Membrane	25 mils	25 mils	25 mils	25 mils
Intermediate	—	15 mils	25 mils	30 mils
Top Coat	15 mils	15 mils	15 mils	20 mils
Sand Aggregate	10-15 lbs / 100 sf / coat	10-15 lbs / 100 sf / coat	10-15 lbs / 100 sf / coat	10-15 lbs / 100 sf / coat
Total	40 mils	55 mils	65 mils	75 mils
Warranty				

COMPONENTS	
Q 152 Primer	Primer
Q 182 Primer	Primer
Q 252 Membrane	Membrane
Q 372 Intermediate / Top Coat	Aromatic: intermediate coat, or top coat for interior (non-UV) areas
Q 582 UV Top Coat	Aliphatic: UV-stable top coat for exterior, sun-exposed areas

Mil thicknesses are Qualideck's published system builds (qualideck.com, Advanced Polymer Technology). Warranty years by system (medium and heavy duty 5 years, extra heavy duty 7, extreme duty 10) as offered through Altitude; terms follow APT's Qualideck warranty, requested through Altitude. Always confirm with the current Qualideck application guide and data sheets. Questions on which system fits your deck? Call Altitude at (303) 482-1010.